

Tabletop cutting machine with a very big inside space – series VN-300 M

The machines of the **Series VN-300 M** are built with a very big inside space. The machine stand is sturdy machine design, all machines are completely powder coated. To be used for Corundum-, Rubber-, Diamond- or CBN-cutting wheels.







VN-300 M

Hand lever machine with fixed table.

VN-300 M2

Hand lever machine with longitudinal- and cross table.



All the machines in this series are certified with the CE mark in accordance with EC guideline 2006/42EG.

Characteristics:

- Max. cutting wheel diameter 300 mm
- ② Side openings for bar material
- 3 Hand lever with clamping for longitudinal cut

External, mobile water tank with dirt filter

V = 80 I, special design with mist filter

Compact control panel with automatic voltage detection

230/380/400/ 460 V-50/60 Hz

Corrosion protected aluminium T-slot table

W x L = 350 x 250 mm; VN-300 M2 ross table equipped with stainless steel labyrinth

Optional:

- Infinitely variable speed control
- Laser device
- Collection basket for small parts
- Base cabinet
- Belt filter and magnetic filter
- Mist filter
- Side movement with scale wheel
- Different clamping devices
- Cutting wheels



Tabletop cutting machine with a very big inside space – series VN-300 M

Technical details:

		VN-300 M	VN-300 M2
Main drive with electronic brake		4.0 kW	4.0 kW
Max. cutting wheel size		300 x 2.8 x 32 mm	300 x 2.8 x 32 mm
Circumferential fixed speed		2,865 1/min 45 m/s	45 m/s
Circumferential variable speed*		1,590 - 3,200 1/min 25 - 63 m/s	25 – 70 m/s
T-Slots Machine table	Width x Depth 5 T-slots	350 x 250 mm 14 mm DIN 650	350 x 250 mm 14 mm DIN 650
Z-axis-cutting wheel shift by hand lever		200 mm	200 mm
X-axis-longtitudinal table of machine shift by servo-axis by hand wheel		-	285 mm
Y-axis-longtitudinal table of machine shift by hand wheel		_	40 mm
Max. material dimension (Width x Height x Depth)		350 x 300 x 350 mm	350 x 300 x 350 mm
Coolant pump		50 l/min	50 l/min
water box		approx. 80 I	approx. 80 I
Interior lighting 24 VDC		LED 7 W	LED 7 W
Machine dimension with hood closed (Width x Height x Depth)		778 x 1,560 x 850 mm	778 x 1,560 x 850 mm
Weight		225 kg	225 kg
Electrical supply data		4.5 kW / 16 A	4.5 kW / 16 A

^{*}optional

Everything from a single source:

Thanks to our integration into the **Pütz Group** and the resulting **synergy effects** we are able to offer you not just production and specialist cutting-off machines but also the appropriate testing technology to test surfaces as well as for dimensional accuracy.

Sampas + Silvercut GmbH

Bahnhofstraße 8/1 74821 Mosbach GERMANY info@silvercut.de

Phone: +49 6261 9726-0 Fax: +49 6261 9726-10

www.silvercut.de

